

CLN-18G40G-3050-K is a Low Noise Amplifier providing a gain of 30 dB with a noise figure of 5.0 dB. The compact size and modularity makes it ideal for a wide range of applications.

Features:

- Frequency Range: 18-40 GHz
- Gain: 30 dB Min
- Noise Figure: 5.0 dB Max
- Solder filtered pins for DC connection
- Low VSWR, unconditional stable


Specifications:


Frequency:	18.0-40.0 GHz
Gain:	30 dB Min
Gain Flatness:	±2.5 dB Max
Noise Figure:	5.0 dB Max
Output P1dB:	10 dBm Min
Output IP3:	19 dBm Typ
VSWR Input:	2.5:1 Max
VSWR Output:	2.5:1 Max
DC Voltage:	+9 V to +15 V DC
DC Supply Current:	200 mA Typ
RF Connector:	2.92mm female

Environmental Ratings:

Temperature:	-40°C to +75 °C Operating -55 °C to +125 °C Non-Operating
Vibration:	MIL-STD-202F, Method 204D Cond. B
Altitude:	MIL-STD-202F, Method 105C Cond. B
Temperature Cycle:	MIL-STD-202F, Method 107D Cond. A

Mechanical Outline(Inches):



Low Noise Amplifier CLN-18G40G-3050-K			
DRAWN:	DWG NO.:	REV CODE: Rev.1.0	 www.connphy.com sales@connphy.com
CHECKRD:	DATE: 14/05/15	SHEET : 1 OF 1	
ISSUED:	SIZE: A	SCALE : N / A	
			Notes: SPEC ARE SUBJECT TO CHANGE WITHOUT NOTICE.