


**CMP-23G28G-2424-S** is a wideband medium power amplifier providing up to 24 dBm and a gain of 24 dB. The compact size and modularity makes it ideal for a wide range of applications.

**Features:**

- Frequency Range: 23 to 28 GHz
- P1dB: 24 dBm Min
- Flat Small Signal Gain: 24 dB Min
- Small size, low cost
- Unconditionally Stable

**Mechanical Outline(Inches) :**




**Specifications:**

Frequency:	23.0-28.0 GHz
Gain:	24 dB Min
Gain Flatness:	±1.0 dB Max
Output P1dB:	24 dBm Min
VSWR Input:	2.0:1 Max
VSWR Output:	2.5:1 Max
DC Voltage:	+12V ±5% DC
DC Supply Current:	600 mA Typ
RF Connectors:	2.92mm Female

**Environmental Ratings:**

Temperature:	-40°C to +75 °C Operating -55 °C to +125 °C Non-Operating
Vibration:	MIL-STD-202F, Method 204D Cond. B
Altitude:	MIL-STD-202F, Method 105C Cond. B
Temperature Cycle:	MIL-STD-202F, Method 107D Cond. A

Medium Power Amplifier CMP-23G28G-2424-S			
DRAWN:	DWG NO.:	REV CODE: Rev.1.0	 <a href="http://www.connphy.com">www.connphy.com</a> <a href="mailto:sales@connphy.com">sales@connphy.com</a>
CHECKRD:	DATE: 15/07/15	SHEET : 1 OF 1	
ISSUED:	SIZE: A	SCALE : N / A	
			Notes: SPEC ARE SUBJECT TO CHANGE WITHOUT NOTICE.