**ZBS-0.01G26.5G-3C** is a rugged zero bias schottky detector, designed to operate over the 0.01-26.5GHz frequency range, with compact size, and also performs with low insertion loss and low VSWR. The model could be used for many applications, radar system, 5G telecom, poswer masurement, millimeter system, etc.

## **Specifications:**

Freq. Range: Freq. Response:

VSWR:

	1.5 -26.5GHz
Max Input Power:	100mW
Low Level Sensitivity:	0.5mV/uW
Power sensitivity:	-30 dBm
Output polarity:	Negtive. Positive output available, plus P to the end.
Input Connector:	3.5 male
Output Connector:	SMC female
Dimension:	1.45 inch x 0.4 inch dia

0.01-26.5 GHz

0.5dB -20GHz 0.8dB -26.5GHz

1.35 -20GHz



## **Environmental Ratings:**

Temperature:	-55ºC to +85 ºC Operating		
	-65 ºC to +100 ºC Non-Operating		
Vibration:	MIL-STD-202F, Method 204D Cond. B		
Altitude:	MIL-STD-202F, Method 105C Cond. B		
Temperature Cycle:	MIL-STD-202F, Method 107D Cond. A		

Zero Bias Schottky Detector ZBS-0.01G26.5G-3C				
DRAWN:	DWG NO.:	REV CODE: Rev.1.0	<b>CONNPHY</b> Microwave Inc.	
CHECKRD:	DATE: 21/04/15	SHEET : 1 OF 1	www.connphy.com sales@connphy.com	
ISSUED:	SIZE:	SCALE : N / A	Notes: SPEC ARE SUBJECT TO CHANGE WITHOUT NOTICE.	