

CDPS-0.25G0.5G-360-8 is an 8-Bit Digital Phase Shifter that operates over the 0.25 GHz to 0.5 GHz frequency range. This model offers 360° of phase shift with an LSB of 1.4°.

Features:

- 0.25-0.5 GHz
- 1.4°LSB,360°Range
- TTL Driver

Specifications:

| | |
|-----------------------|-----------------------------------|
| Frequency Range: | 0.25-0.5GHz |
| Insertion Loss: | 4.5 dB Max |
| Number of Bits: | 8 |
| Significant Bit(LSB): | 1.4° |
| Phase Range: | 360° |
| VSWR: | 1.8:1 Max |
| Operating Power: | +20 dBm Max |
| Power Handling: | +30 dBm Max |
| Switching Time: | 500 nsec Max |
| Control Logic: | TTL |
| Power supply: | +5V dc @ 300 mA -5V dc @ 300mA |


Environmental Ratings:


| | |
|--------------------|--|
| Temperature: | -45°C to +85 °C Operating -55 °C to +85°C Non-Operating |
| Vibration: | MIL-STD-202F, Method 204D Cond. B |
| Altitude: | MIL-STD-202F, Method 105C Cond. B |
| Temperature Cycle: | MIL-STD-202F, Method 107D Cond. A |

Mechanical Specifications:


| Parameter | Specification |
|----------------------|--------------------------|
| Dimensions WxHxD | 3.975X1.574X0.629 inches |
| RF Connectors In/Out | SMA-Female |
| DC Connector | D-SUB 15 Pin(Female) |
| Material | Aluminum |

DC Connector PIN Assignment:

| Pin | Function | Pin Definition |
|------|-----------|---|
| 1-8 | Bit1-Bit8 |  |
| 9-12 | NC | |
| 13 | +5V | |
| 14 | -5V | |
| 15 | GND | |

| 8-Bit Digital Phase Shifter CDPS-0.25G0.5G-360-8 | | | |
|---|-------------------|----------------------|---|
| DRAWN: | DWG NO.: | REV CODE: Rev.1.0 |  www.connphy.com sales@connphy.com |
| CHECKRD: | DATE: 08/07/15 | SHEET : 1 OF 2 | |
| ISSUED: | SIZE: A | SCALE : N / A | |
| | | | Notes: SPEC ARE SUBJECT TO CHANGE WITHOUT NOTICE. |

Mechanical Outline(Inches) :



Truth Table :

| Control Voltage TTL Input for 8 bits resolution | | | | | | | | Phase Shift RFin - Rfout |
|---|-------|-------|-------|-------|-------|-------|-------|-----------------------------|
| Bit 1 | Bit 2 | Bit 3 | Bit 4 | Bit 5 | Bit 6 | Bit 7 | Bit 8 | |
| 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | Reference |
| 0 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1.40° |
| 1 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 2.81° |
| 1 | 1 | 0 | 1 | 1 | 1 | 1 | 1 | 5.62° |
| 1 | 1 | 1 | 0 | 1 | 1 | 1 | 1 | 11.25° |
| 1 | 1 | 1 | 1 | 0 | 1 | 1 | 1 | 22.50° |
| 1 | 1 | 1 | 1 | 1 | 0 | 1 | 1 | 45.00° |
| 1 | 1 | 1 | 1 | 1 | 1 | 0 | 1 | 90.00° |
| 1 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 180.00° |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 358.60° |

Environmental Ratings:

Temperature: -45°C to +85 °C Operating
 -55 °C to +85°C Non-Operating

Vibration: MIL-STD-202F, Method 204D Cond. B

Altitude: MIL-STD-202F, Method 105C Cond. B

Temperature Cycle: MIL-STD-202F, Method 107D Cond. A

8-Bit Digital Phase Shifter CDPS-0.25G0.5G-360-8

| | | |
|----------|-------------------|----------------------|
| DRAWN: | DWG NO.: | REV CODE: Rev.1.0 |
| CHECKRD: | DATE: 08/07/15 | SHEET : 2 OF 2 |
| ISSUED: | SIZE: A | SCALE : N / A |

CONNPHY
 Microwave Inc.
www.connphy.com
sales@connphy.com

Notes: SPEC ARE SUBJECT TO
 CHANGE WITHOUT NOTICE.