


SDL-0.5G6G-20-50-P is a high performance, high dynamic range DLVA with smart size, which ensures itself could be used in various receiving applications. Main features as listed:

- 1). frequency range: 0.5G~6G
- 2). dynamic range -77 to +0dBm
- 3). logging slop: 50mV/dB, or consult factory if customize
- 4). compact size

Mechanical Outline:



Unit: Inch


Specifications:

Frequency: 0.5 to 6GHz
 Dynamic Range: -77 to 0 dBm
 Max input WO damage: +20dBm
 Rise time: 10nsec typ 14nsec max
 Fall time: 15nsec typ 25nsec max
 Recover time: 100nsec max
 Input VSWR: 2.5:1 max
 Log slope: 50mV/dB (or consult factory if customize)
 Log Accuracy: ±2dB max
 Load Impedance: 100ohm
 Power supply : 200mA @ +12V
 100mA @ -12V
 TSS: -80dBm max
 Pulse Reponse: 30nsec to 100us
 Baseline noise: 25mV RMS max
 DC offset: 100±50mV
 Connector: SMA female
 Material: stainless steel

Environmental Ratings:

Temperature: -40°C to +80 °C Operating
 -65 °C to +100 °C Non-Operating
 Vibration: MIL-STD-810F, Method 514.5 Cond. B
 Altitude: MIL-STD-202F, Method 105C Cond. B
 Temperature Cycle: MIL-STD-202F, Method 107D Cond. A

SDL-0.5G6G-20-50-P		
DRAWN:	REV CODE : 152221	SCALE : N / A
CHECKRD:	DATE: 12/01/13	SIZE: A
ISSUED:	DWG NO.:	SHEET : 1 OF 1



CONNPHY
Microwave Inc.

www.connphy.com
sales@connphy.com